F321281

Page Top

ONLINE CERTIFICATIONS DIRECTORY

SEARCH TOOL. REGISTER NOW! OLEARNMORE

ZPMV2.E321281 Wiring, Printed - Component

If you notice a change to your ZPMV2 Listing Card, click here to learn more.

For enhanced search functionality, please visit UL's <u>iQ™ Family of Databases</u>.

Click on a product designation for complete information.

Page Bottom

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

BETA LAYOUT GMBH

IM AARTAL 14

65326 AARBERGEN, GERMANY

	Cond Width				Max			Max			\square
		Min	Cond	SS/	Area	Solder		Oper		Meets	с
	Min	Edge	Thk	DS/	Diam	Limits		Temp	Flame	UL796	т
Туре	mm(in)	mm(in)	mic(mil)	DSO	mm(in)	С	sec	С	Class	DSR	I
Multilayer printed wiring boards.											
м	0.075 (0.003)	0.075 (0.003)	18 (0.71) Int:35	DS	50.8 (2.0)	288	20	130	V-0	All	*
Multilayer printed wiring boards with an embedded RFID module, flammability only Recognition.											
E	-	-	-	DS	-	288	20	-	V-0	-	-
Single layer printed wiring boards.											
s	0.075 (0.003)	0.075 (0.003)	18 (0.71)	DS	50.8 (2.0)	288	20	130	V-0	All	*
Single layer printed wiring boards with an embedded RFID module, flammability only Recognition.											
F	-	-	-	DS	-	288	20	-	V-0	-	-

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or tradename "BL" or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2018-01-15

Questions?

<u>Print this page</u>

<u>Terms of Use</u>

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".

1 von 1